

KEP® 270

Ethylene Propylene Diene Terpolymer

Kumho Polychem Co., Ltd.

Message:

Features:

High mooney viscosity & medium vulcanization speed, high filler loading

Applications:

Heat resistant hose, washing machine hose, window seals, various types of automobile parts

| General Information | | |
|-------------------------------------|-------------------------|------|
| Features | High Viscosity | |
| | Vulcanizable | |
| Uses | Automotive Applications | |
| | Hose | |
| | Seals | |
| Forms | Bale | |
| Physical | Nominal Value | Unit |
| Mooney Viscosity (ML 1+4, 125°C) | 71 | MU |
| Ethylene Content | 57.0 | wt% |
| Ethylidene Norbornene (ENB) Content | 4.5 | wt% |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

