

# Shanghai Potomer SG8

Rigid Polyvinyl Chloride

Shanghai Potomer International Trade Co., Ltd.

## Message:

PVC suspension Resin is Calcium Carbide base, mainly used as sheet, pipe, window profiles and other molded parts.

APPLICATIONS: fittings, electrical housings, bottles, rigid film, rigid foam

General Information	
Features	High Rigidity
Uses	Bottles
	Electrical Housing
	Film
	Fittings
	Foam
Processing Method	Calendering
	Extrusion
	Injection Molding

Physical	Nominal Value	Unit
Apparent Density	> 0.48	g/cm <sup>3</sup>
K (wear) Factor	55.0 to 59.0	
Sieve Analysis		
0.063mm sieve	> 90	%
0.25mm sieve	< 2.0	%
Viscosity	73.0 to 86.0	cm <sup>3</sup> /g
Volatile Matter	< 0.40	%
Fish Eye	< 30.0	pcs/400 cm <sup>2</sup>
Impurities	< 20.0	pcs
Polymerization	650 to 750	
Whiteness - after 10min (160°C)	> 70	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

