# SILVER® SA-5321

## Polyolefin

### Guangdong Silver Age Sci & Tech. Co., Ltd

#### Message:

SILVER® SA-5300 is low—smoke halogen-free flame retardant compound for cable which is polyolefin based material containing inorganic flame retardant, antioxidant,lubricant, etc. It is non-halogen, non-heavy metal, can pass RoHS. The series compound which can be radiation cross—linking makes it higher performance for temperature—resistant, better mechanical property and better insulating property. It can be used for power—cable, the cable for metro, and the cable for nuclear power plant, and so on. Low Smoke Zero Halogen Flame Retardant Polyolefin Series Crosslinking by irradiation Series Characteristics: low smoke zero halogen Applications: wire and cable, plug, electronic line and so on

| General Information         |                                    |                |  |
|-----------------------------|------------------------------------|----------------|--|
| Additive                    | Antioxidant                        |                |  |
|                             | Flame Retardant                    |                |  |
|                             | Lubricant                          |                |  |
|                             |                                    |                |  |
| Features                    | Antioxidant                        |                |  |
|                             | Flame Retardant                    |                |  |
|                             | Halogen Free                       |                |  |
|                             | Irradiation Crosslinkable          |                |  |
|                             | Low Smoke Emission                 |                |  |
|                             | Lubricated                         |                |  |
|                             |                                    |                |  |
| Uses                        | Electrical Parts                   |                |  |
|                             | Electrical/Electronic Applications |                |  |
|                             | Nuclear Power Applications         |                |  |
|                             | Plugs                              |                |  |
|                             | Wire & Cable Applications          |                |  |
|                             |                                    |                |  |
| RoHS Compliance             | RoHS Compliant                     | RoHS Compliant |  |
| Physical                    | Nominal Value                      | Unit           |  |
| Specific Gravity            | 1.43                               | g/cm³          |  |
| рН                          | 6.8                                |                |  |
| Halogenidric Acid Emissions | 3.10                               | mg/g           |  |
| Smoke Density               |                                    |                |  |
| Flame                       | 55                                 |                |  |
| Non-flame                   | 160                                |                |  |
| Toxicity                    | 1.30                               |                |  |
| Electrical Conductivity     | 1.80                               | μS/mm          |  |

| Hardness                                   | Nominal Value | Unit    |
|--|---------------|---------|
| Durometer Hardness                         |               |         |
| Shore A                                    | 93            |         |
| Shore D                                    | 48            |         |
| Mechanical                                 | Nominal Value | Unit    |
| Tensile Strength                           | 11.7          | MPa     |
| Tensile Elongation (Break)                 | 210           | %       |
| Aging                                      | Nominal Value | Unit    |
| Change in Tensile Strength (180°C, 168 hr) | -2.7          | %       |
| Change in Ultimate Elongation (180°C, 168  |               |         |
| hr)  | -14           | %       |
| Electrical                                 | Nominal Value | Unit    |
| Volume Resistivity                         | 5.0E+14       | ohms•cm |
| Dielectric Strength                        | 37            | kV/mm   |
| Flammability                               | Nominal Value | Unit    |
| Oxygen Index                               | 31            | %       |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

