

HYPERIER® IP1104

Thermoplastic

LG Chem Ltd.

Message:

HYPERIER® is the nanocomposite alloy made of a nanometer scale inorganic layered silicates (clay) and various polymers.

The nanocomposite alloy enables the formation of continuous and lamellar shape of barrier membrane.

It is usually blended with polyolefin (HDPE, LDPE or PP) for blow molding.

Benefits and Applications:

Various applications from agricultural packaging to fuel tanks and containers

Cost-effectiveness

Utilizes current mono-layer equipments and molds

Excellent Emission Barrier to most of fuel types and agrochemicals

Good mechanical property especially at the low temperature

Good insert coverage

SGS, FDA compliance

IP-1104:

Applicable bottle size: 20 to 220 L

Application: Large Drum, SORE® Fuel Tank

General Information			
Features	Barrier Resin		
	High Impact Resistance		
	Low Temperature Resistant		
Uses	Blending		
	Containers		
	Fuel Tanks		
	Membranes		
	Packaging		
Agency Ratings		FDA Unspecified Rating	
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.998	g/cm ³	Internal Method
Thermal	Nominal Value	Unit	
Melting Temperature	213	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

