

Propilven S-801

Polypropylene Homopolymer

Propilven, S.A.

Message:

Propilven S-801 grade is a polypropylene homopolymer designed for extrusion of multifilaments, cut fiber and low height thread systems.

Special Features:

Controlled rheology

General Information	
Features	Controlled Rheology Food Contact Acceptable Homopolymer
Uses	Fibers Filaments
Forms	Pellets
Processing Method	Extrusion Fiber (Spinning) Extrusion

Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR)	20	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	30.0	MPa	ASTM D638
Flexural Modulus	1200	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	30	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	100	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT