

Hy-Vin® VX390

Flexible Polyvinyl Chloride

INEOS Compounds

Message:

Hy-Vin® VX390 is a Flexible Polyvinyl Chloride material. It is available in Europe.

Important attributes of Hy-Vin® VX390 are:

Good Flexibility

Good Processability

General Information			
Features	General Purpose		
	Good Flexibility		
	Good Moldability		
Uses	General Purpose		
Appearance	Colors Available		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.36	g/cm ³	BS 2782
Water Absorption (Saturation)	0.25	%	BS 2782 430A
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A, 15 sec, 23°C)	90		BS 2782
BS Softness	17	°	BS 2782
Cold Bend	< -20	°C	BS 2782
Cold Flexibility	-10	°C	BS 2782
Extrusion	Nominal Value	Unit	
Cylinder Zone 1 Temp.	170	°C	
Cylinder Zone 2 Temp.	170	°C	
Cylinder Zone 3 Temp.	170	°C	
Die Temperature	170	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT