THERMOLAST® K TF9WCS (Series: DW/CS)

Thermoplastic Elastomer

KRAIBURG TPE

Message:

The DW/CS Series is your material solution for applications in contact with drinking water as well as excellent compression set. The compounds are approved in accordance with all relevant European drinking water standards - DVGW, W270, KTW, WRAS, ACS.

Typical applications

Seals, functional and designelements in sanitary sector

Material advantages

General Information

Easy coloring (compounds in natural colors)

For injection molding and extrusion

Smooth surface and repels dirtand lime deposit

General Information				
Features	Good Colorability			
Uses	Potable Water Applications			
	Seals			
Agency Ratings	ACS Unspecified Rating			
	DVGW W270			
	KTW Unspecified Rating			
	WRAS Unspecified Rating			
Appearance	Natural Color			
Processing Method	Extrusion			
	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Density	0.950	g/cm³	ISO 1183	
Hardness	Nominal Value	Unit	Test Method	
Shore Hardness (Shore A)	87		ISO 7619	
Elastomers	Nominal Value	Unit	Test Method	
Tensile Stress ¹ (Yield)	15.0	МРа	ISO 37	
Tensile Elongation ² (Break)	300	%	ISO 37	
Tear Strength ³	30	kN/m	ISO 34-1	
Compression Set ⁴			ISO 815	
23°C, 72 hr	40	%		
70°C, 24 hr	65	%		
Extrusion	Nominal Value	Unit		
Drying Temperature	60.0 to 80.0	°C		
Drying Temperature Drying Time	60.0 to 80.0 2.0 to 4.0	°C hr		

Cylinder Zone 2 Temp.	180	°C	
Cylinder Zone 3 Temp.	200	°C	
Die Temperature	200 to 230	°C	
NOTE			
1.	Type S2, 200 mm/min		
2.	Type S2, 200 mm/min		
3.	Method Bb, Angle (Nicked)		
4.	Method A		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

