Unichem 6534

Polyvinyl Chloride

Colorite Polymers

Message:

Unichem 6534 is a Polyvinyl Chloride product. It can be processed by injection molding and is available in Asia Pacific, Europe, or North America.

| General Information | | | |
|--------------------------------------|-------------------|-------|-------------|
| Features | General Purpose | | |
| Uses | General Purpose | | |
| Appearance | Clear/Transparent | | |
| Processing Method | Injection Molding | | |
| Physical | Nominal Value | Unit | Test Method |
| Specific Gravity | 1.23 | g/cm³ | ASTM D792 |
| Hardness | Nominal Value | Unit | Test Method |
| Durometer Hardness (Shore A, 10 sec) | 65 | | ASTM D2240 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Modulus - 100% Secant | 4.27 | MPa | ASTM D638 |
| Tensile Strength | 11.5 | MPa | ASTM D638 |
| Tensile Elongation (Break) | 440 | % | ASTM D638 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

