

# Evermore PUR SA-6010P

Polyurethane  
Evermore Chemical Industry Co., Ltd.

Message:  
Evermore PUR SA-6010P is a Polyurethane product. It is available in Asia Pacific. Primary characteristic: good flexibility.

General Information			
Features	Low Temperature Flexibility		
Uses	Synthetic Leather		
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	1.57 to 3.14	MPa	ASTM D412
Tensile Strength (Yield)	9.81 to 24.5	MPa	ASTM D412
Tensile Elongation (Break)	300 to 600	%	ASTM D412
Fill Analysis	Nominal Value	Unit	Test Method
Melt Viscosity (25.0°C)	80.0 to 120	Pa·s	ASTM D3835
Additional Information	Nominal Value	Unit	Test Method
Non-Volatile Content	58 to 62	%	
Solvents	DMF, TOL		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT