

T-Blend® TPR-F65

Styrene Ethylene Butylene Styrene Block Copolymer

TSRC Corporation

Message:

T-Blend® TPR-F65 is a Styrene Ethylene Butylene Styrene Block Copolymer (SEBS) product. It is available in Asia Pacific. Applications of T-Blend® TPR-F65 include film, medical/healthcare, packaging and sporting goods.

Characteristics include:

- Eco-Friendly/Green
- Good Flexibility
- Good Processability
- Good Weather Resistance
- Low Temperature Resistant

General Information			
Features	Good Flexibility		
	Good Processability		
	Good Sterilizability		
	Good Weather Resistance		
	Low Temperature Resistant		
	Moisture Permeability		
	Non-Toxic		
	Recyclable Material		
	Soft		
Uses	Film		
	Food Packaging		
	Medical/Healthcare Applications		
	Sporting Goods		
Appearance	Blue		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.910 to 0.950	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (180°C/5.0 kg)	7.0	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	64 to 68		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (Break)	6.67	MPa	ASTM D412
Tensile Elongation (Break)	570	%	ASTM D412
Tear Strength	44.1	kN/m	ASTM D624
Injection	Nominal Value	Unit	
Processing (Melt) Temp	160 to 220	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

