Royalene® 677

Ethylene Propylene Diene Terpolymer Lion Copolymer, LLC

Message:

A Highly Extendable ENB Polymer with Heavy Hydrotreated Paraffinic Oil for TPO/TPV and Thermoset Applications

Unique Features

Blends readily with polyolefins for TPO and TPV compounds

Provides enhanced compression set and good color in TPV

Highly extendable

Good aging properties

Good shape retention in extruded applications

Very high molecular weight base polymer

High green strength over a broad temperature range

Useful for making low hardness compounds

Extended with a white, hydrotreated paraffinic oil

Applications

TPO and TPV

Automotive applications

Mechanical goods

Hose tubes, Profile extrusions

General Information					
Features	Oil-filled				
	High molecular weight				
	High strength				
	Hardness, low				
	Medium wide molecular weight distribution				
Uses	Thermoforming Applications				
	Pipe				
	Pipe fittings				
	Mixing				
	Machine/mechanical parts				
	Application in Automobile Field				
Agency Ratings	FDA 21 CFR 177.2600				
	FDA not rated				
Appearance	White-like				
Forms	bag				
Processing Method	Extrusion				
	Profile extrusion molding				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	0.880	g/cm³	ASTM D792		

Mooney Viscosity ¹ (ML 1+4, 125°C)	50	MU	Internal method
Ethylidene Norbornene (ENB) Content	4.5	wt%	Internal method
Oil Type (Paraffinic Oil)	50.0	phr	Internal method
Stabilizer	Non-staining		
Molecular Weight Distribution	Medium		Internal method
Volatile Matter		wt%	Internal method
Additional Information			
E/P weight ratio, internal standard ZS 12	31: 70/30		
NOTE			
1	Unmilled		

Unmilled

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

