

# Qenos PP PPR 1060F

Polypropylene Homopolymer

Qenos Pty Ltd

## Message:

PPR 1060F is a medium flow, high tenacity extrusion grade of Polypropylene homopolymer.

PPR 1060F is typically used for production of stretched weaving tapes, bailer twine and industrial lashings. Suitability for use in any application should be determined by appropriate performance testing.

PPR 1060F is suitable for food contact applications and conforms to the requirements of AS2070-1999, Plastics Materials for Food Contact Use.

General Information			
Features	Food Contact Acceptable		
	Homopolymer		
	Medium Flow		
Uses	Industrial Applications		
	Tape		
	Twine		
Agency Ratings	AS 2070-1999		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.902	g/cm <sup>3</sup>	ASTM D792
Melt Mass-Flow Rate (MFR)			ASTM D1238
230°C/2.16 kg	4.0	g/10 min	
230°C/5.0 kg	18	g/10 min	
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	40.0	MPa	ASTM D638
Flexural Modulus	1700	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	100	J/m	ASTM D256A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT