

# FM® 99

Epoxy; Epoxide  
Cytec Industries Inc.

### Message:

FM® 99 is a modified epoxy-based adhesive film designed for surfacing composite structures. It provides a high quality, ready-to-paint surface finish with no core mark off. Its 250°F/350°F (121°C/177°C) dual cure capability makes FM 99 surfacing film suitable for surfacing a wide variety of composite prepregs and materials. FM 99 surfacing film is supplied as a thin film with a random mat carrier. It can also be supplied unsupported or with various copper, aluminum and other metallic screens and foils for lightning strike applications.

Suggested Applications:  
Co-curing and surfacing of 250°F and 350°F (121°C and 177°C) curing epoxy/graphite, epoxy/glass and epoxy/Kevlar prepregs.

| General Information |                      |
|---------------------|----------------------|
| Features            | Good Surface Finish  |
|                     | Humidity Resistant   |
|                     | Paintable            |
| Uses                | Coating Applications |
| Appearance          | Brown                |
| Forms               | Film                 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT