

# TOTAL Polypropylene PPH 3620WZ

Polypropylene Homopolymer

TOTAL Refining & Chemicals

Message:

TOTAL Polypropylene 3620WZ is engineered with nucleation to provide fast cycle time and improve contact clarity in thin wall multi-cavity molds. TOTAL Polypropylene 3620WZ contains an antistat that will help protect molded parts from dust accumulation. TOTAL Polypropylene 3620WZ has passed USP Class VI testing, an all ingredients meet the chemical registration requirements of TSCA (U.S.) and DSL (Canada). TOTAL Polypropylene 3620WZ complies with all applicable FDA regulations for food contact applications. TOTAL Polypropylene 3620WZ is particularly well suited for caps, closures, medical syringes and thin wall containers.

General Information			
UL YellowCard	E66261-247989		
Additive	Antistatic		
	Nucleating Agent		
Features	Antistatic		
	Fast Molding Cycle		
	Nucleated		
Uses	Caps		
	Closures		
	Medical/Healthcare Applications		
	Thin-walled Parts		
Agency Ratings	EC 1907/2006 (REACH)		
	FDA Food Contact, Unspecified Rating		
	USP Class VI		
RoHS Compliance	RoHS Compliant		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.905	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	12	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	107		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	1720	MPa	ASTM D638
Tensile Strength (Yield)	37.2	MPa	ASTM D638
Tensile Elongation (Yield)	12	%	ASTM D638
Flexural Modulus	1590	MPa	ASTM D790

Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	27	J/m	ASTM D256A
Unnotched Izod Impact (23°C)	850	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	127	°C	ASTM D648
Melting Temperature	166	°C	DSC

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

