

Shuang-Bang CD-1060S

Polyurethane

Shuang-Bang Industrial Corp.

Message:

One component PU Resins

PU membrane is produced by coating the resin on substrate and drying it to vaporize the solvent adequately. The membrane gives soft hand-feel and dry surface, and offers waterproof and windproof properties. Using one component type PU resin alone with adequate crosslinker for yarn fixation, following by drying process to vaporize solvent adequately, could form high yarn-bonding membrane.

Shoes, leather bag, ready-make clothes

Blocking resistance, high water resistance, good hand-feel

Surface modifier for high moisture-permeability fabrics. Could increase water pressure without reducing moisture-permeability. Dry hand-feel.

General Information		
Features	Crosslinkable	
Uses	Adhesives	
	Coating Applications	
	Footwear	
Appearance	Off-White	
Additional Information	Nominal Value	Unit
Solvents	DMF/MEK/TOL	
Uncured Properties	Nominal Value	Unit
Color	Off White	
Solids Content	29 to 31	%
Viscosity (25°C)	15 to 30	Pa·s
Cured Properties	Nominal Value	Unit
Tensile Modulus (100% Secant)	3.43 to 5.39	MPa
Tensile Strength	> 11.8	MPa
Tensile Elongation at Break	> 400	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT