

Spartech Polycom E65390

Polyvinyl Chloride

Spartech Polycom

Message:

Spartech Polycom, Kearny is the first choice for compounds meeting the stringent requirements of Spiral Hose, Automotive, Housewares, Farm Equipment, Coated Fencing and numerous other applications including Lawn & Garden Wheels. Our products are engineered specifically for each application, as well as for each customer's equipment, including the demands of today's sophisticated manufacturing processes.

| General Information | | | |
|--------------------------------------|---------------------------------|-------------------|-------------|
| Filler / Reinforcement | Filler | | |
| Features | General | | |
| Uses | Pipe fittings | | |
| | Weather-resistant sealing strip | | |
| | Profile | | |
| Processing Method | Profile extrusion molding | | |
| Physical | Nominal Value | Unit | Test Method |
| Specific Gravity | 1.30 | g/cm ³ | ASTM D792 |
| Hardness | Nominal Value | Unit | Test Method |
| Durometer Hardness (Shore A, 10 sec) | 90 | | ASTM D2240 |
| Elastomers | Nominal Value | Unit | Test Method |
| Tensile Stress (100% Strain) | 14.5 | MPa | ASTM D412 |
| Tensile Strength (Yield) | 21.0 | MPa | ASTM D412 |
| Tensile Elongation (Break) | 360 | % | ASTM D412 |
| Additional Information | Nominal Value | Unit | |
| Stock Temperature | 188 | °C | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT