

Sinvicomp SRF1707

Rigid Polyvinyl Chloride

Teknor Apex Asia Pacific PTE. LTD.

Message:

Sinvicomp SRF1707 is a Rigid Polyvinyl Chloride material. It is available in Asia Pacific for injection molding. Primary attribute of Sinvicomp SRF1707: Impact Resistant.

Typical application of Sinvicomp SRF1707: Engineering/Industrial Parts

General Information			
Features	Good Impact Resistance		
Uses	Fittings		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.46	g/cm ³	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield)	45.1	MPa	ASTM D638
Tensile Elongation ² (Break)	110	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	59	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	93.0	°C	ASTM D1525
Thermal Stability ³ (190°C)	> 30	min	BS 2782
NOTE			
1.	500 mm/min		
2.	250 mm/min		
3.	Congo Red		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT