

Huafon JF-A-WV7020

Polyurethane

Huafon Group Co., Ltd.

Message:

Non-Yellowing Type

Characteristics

Non-yellowing type PU resin for adhesive layer, cold resistance, hydrolysis resistance, solvent resistance, swelling resistance, good water pressure resistance, good water vapor permeability, good washing fastness, strong adhesive strength, can be used together with ""JF-S-WV7030"".

Applications

Micro fibre, Garments, Shoes

General Information		
Features	Good Adhesion	
	Hydrolysis Resistant	
	Low Temperature Resistant	
	Moisture Permeability	
	Solvent Resistant	
Uses	Footwear	
	Textile Applications	
Additional Information	Nominal Value	Unit
Solvents	DMF/IBA	
Uncured Properties	Nominal Value	Unit
Solids Content	34 to 36	%
Viscosity (25°C)	60 to 120	Pa·s
Cured Properties	Nominal Value	Unit
Tensile Modulus (100% Secant)	2.00 to 3.00	MPa
Tensile Strength	> 20.0	MPa
Tensile Elongation at Break	> 600	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT