

# Axiall PVC 7751

Rigid Polyvinyl Chloride

Axiall Corporation

## Message:

Georgia Gulf 7751 is a vertical blind profile exterior compound requiring impact strength and toughness, colorability, dimensional stability, UV color stability, and easy processing for thin parts at fast rates.

General Information			
Features	Good Color Stability Good Colorability Good Dimensional Stability Good Impact Resistance Good Processability Good Toughness		
Uses	Outdoor Applications Profiles		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.50	g/cm <sup>3</sup>	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	112		ASTM D785
Durometer Hardness (Shore D)	81		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	3220	MPa	ASTM D638
Tensile Strength (Yield)	40.5	MPa	ASTM D638
Flexural Modulus	3070	MPa	ASTM D790
Flexural Strength	74.2	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
3.18 mm	210	J/m	
6.35 mm	140	J/m	
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	69.5	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

