

LNP™ THERMOCOMP™ UF008AR compound

Polyphthalamide

SABIC Innovative Plastics Europe

Message:

LNP THERMOCOMP UF008AR is a compound based on Polyphthalamide resin, containing Glass Fiber. Added features include; Mold Release.

Also known as: LNP* THERMOCOMP* Compound UF-1008 A MR

Product reorder name: UF008AR

General Information			
UL YellowCard	E45329-101284057		
Filler / Reinforcement	Glass Fiber		
Additive	Mold Release		
RoHS Compliance	RoHS Compliant		
Physical	Nominal Value	Unit	Test Method
Density	1.53	g/cm ³	ISO 1183
Molding Shrinkage - Flow	0.14	%	Internal Method
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	14500	MPa	ISO 527-2/1
Tensile Stress (Break)	234	MPa	ISO 527-2/5
Tensile Strain (Break)	2.1	%	ISO 527-2/5
Flexural Modulus ¹	12000	MPa	ISO 178
Flexural Stress	315	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength ² (23°C)	13	kJ/m ²	ISO 180/1A
Unnotched Izod Impact Strength ³ (23°C)	55	kJ/m ²	ISO 180/1U
Thermal	Nominal Value	Unit	Test Method
CLTE			ISO 11359-2
Flow : 23 to 60°C	2.3E-5	cm/cm/°C	
Transverse : 23 to 60°C	5.3E-5	cm/cm/°C	
NOTE			
1.	2.0 mm/min		
2.	80*10*4		
3.	80*10*4		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

