

Hostacom ERC 198N G14008

Polypropylene Copolymer

LyondellBasell Industries

Message:

Hostacom ERC 198N is a 20% mineral filled elastomer modified PP copolymer with high flow, high toughness and good UV resistance. Used for automotive interior trim in particular instrument panels.

General Information	
Filler / Reinforcement	Mineral,20% Filler by Weight
Additive	Impact Modifier UV Stabilizer
Features	Copolymer Good Toughness Good UV Resistance High Flow Impact Modified
Uses	Automotive Instrument Panel Automotive Interior Parts Automotive Interior Trim

Physical	Nominal Value	Unit	Test Method
Density	1.05	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	15	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	19.0	MPa	ISO 527-2
Tensile Strain (Yield)	9.0	%	ISO 527-2
Flexural Modulus	1800	MPa	ISO 178
Flexural Stress	28.0	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength			ISO 180
-30°C	4.0	kJ/m ²	
23°C	30	kJ/m ²	
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (1.8 MPa, Unannealed)	57.0	°C	ISO 75-2/A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT