

Sylvin 8280-60 Black

Polyvinyl Chloride
Sylvin Technologies Incorporated

Message:
Sylvin 8280-60 Black Is A Vinyl Compound Formulated For General Purpose Extrusion Or Molding Applications.

General Information	
Features	General Purpose
Uses	General Purpose
Appearance	Black
Processing Method	Extrusion Injection Molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.37	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	60		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	9.31	MPa	ASTM D638
Tensile Elongation (Break)	360	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	31.5	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	154 to 166	°C	
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	22	%	ASTM D2863

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT