

Network Polymers SMMA MS 200

Styrene Methyl Methacrylate Acrylic Copolymer

Network Polymers, Inc.

Message:

Network Polymers SMMA MS 200 is a Styrene Methyl Methacrylate Acrylic Copolymer product. It is available in North America. Typical application: Food Contact Applications. Primary characteristic: copolymer.

General Information			
Features	Copolymer		
Agency Ratings	FDA 21 CFR 177.1640		
	FDA 21 CFR 177.1830		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.07	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) ¹ (200°C/5.0 kg)	2.0	g/10 min	ASTM D1238
Molding Shrinkage - Flow	0.20 to 0.80	%	ASTM D955
Water Absorption (24 hr)	0.11	%	ASTM D570
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (M-Scale)	75		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ² (Yield)	57.2	MPa	ASTM D638
Tensile Elongation ³ (Yield)	3.0	%	ASTM D638
Flexural Modulus	3130	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (3.18 mm)	16	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	76.1	°C	ASTM D648
Vicat Softening Temperature	97.7	°C	ASTM D1525
Optical	Nominal Value	Unit	Test Method
Transmittance	90.0	%	ASTM D1003
NOTE			
1.	Procedure A		
2.	51 mm/min		
3.	51 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

