

Royalite DKE 450

Acrylic (PMMA) + PVC

Spartech Plastics

Message:

Royalite DKE 450 is an acrylic acid (PMMA) PVC (PMMA PVC) product. It can be processed by vacuum molding and is available in North America. The main features are: flame retardant.

General Information			
Features	Flame retardancy		
Forms	Sheet		
Processing Method	Vacuum forming		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.26	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	110		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	46.9	MPa	ASTM D638
Flexural Modulus	2620	MPa	ASTM D790
Flexural Strength (Yield)	75.8	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
-29°C, 3.18 mm	53	J/m	ASTM D256
23°C, 3.18 mm	640	J/m	ASTM D256
Dart Drop Impact (3.18 mm)	27.1	J	ASTM D3029
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	85.0	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT