

ELASTOSIL® SOLAR 1109 WHITE

Silicone

Wacker Chemie AG

Message:

Silicone Rubber, RTV-1

Photovoltaics, Renewable Energies

General Information			
Uses	Adhesives		
	Bonding		
	Sealants		
	Solar Panels		
Uncured Properties	Nominal Value	Unit	Test Method
Color	White		
Density	1.33	g/cm ³	ISO 1183
Viscosity	700	Pa·s	DIN EN ISO 3219
Cured Properties	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	30		DIN 53505
Tensile Strength	2.10	MPa	DIN 53504
Tensile Elongation at Break	450	%	DIN 53504
Tear Strength	8.50	kN/m	ASTM D624B

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT