

BC PS MG-125

General Purpose Polystyrene

BC Chemical Co., Ltd.

Message:

BC PS MG-125 is a general-purpose polystyrene product. It is available in the Asia-Pacific region. The main characteristics are: flame retardant/rated flame.

General Information			
UL File Number	E74696		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.05	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (200°C/5.0 kg)	9.0	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (L-Scale)	90		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield, 23°C, 3.18 mm)	43.1	MPa	ASTM D638
Tensile Elongation ² (Break, 23°C, 3.18 mm)	2.0	%	ASTM D638
Flexural Modulus ³ (23°C, 3.18 mm)	3040	MPa	ASTM D790
Flexural Strength ⁴ (23°C, 3.18 mm)	68.5	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256A
23°C, 3.18 mm	21	J/m	ASTM D256A
23°C, 6.35 mm	18	J/m	ASTM D256A
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed, 12.7 mm)	83.9	°C	ASTM D648
Vicat Softening Temperature	97.8	°C	ASTM D1525 ⁵
Flammability	Nominal Value		Test Method
Flame Rating			UL 94
1.59 mm	HB		UL 94
3.18 mm	HB		UL 94
Additional Information			
Volatile Content, GC Method: <1500 ppm			
NOTE			
1.	Type 1, 50mm/min		
2.	Type 1, 50mm/min		
3.	15 mm/min		
4.	15 mm/min		
5.	压 力1 (10N)		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

