

Badaflex® TPE-S 30A 1000LD

Thermoplastic Elastomer

Bada AG

Message:

Badaflex® TPE-S 30A 1000LD is a Thermoplastic Elastomer (TPE) material. It is available in Europe.

General Information			
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.990	g/cm ³	ISO 1183
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	30		ISO 868
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	4.50	MPa	ISO 37
Tensile Elongation (Break)	610	%	ISO 37
Tear Strength	9.0	kN/m	ISO 34-1
Compression Set (23°C, 72 hr)	16	%	ISO 815

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT