

Geon™ Vinyl Wire & Cable WJJK501

Flexible Polyvinyl Chloride

PolyOne Corporation

Message:

Geon™ Vinyl Wire & Cable WJJK501 is a Flexible Polyvinyl Chloride product. It can be processed by extrusion coating and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Typical application: Wire & Cable.

Characteristics include:

RoHS Compliant

Flame Retardant

General Information			
Features	Flame Retardant		
Uses	Building Wire Jacketing		
	Wire & Cable Applications		
RoHS Compliance	RoHS Compliant		
Forms	Pellets		
Processing Method	Extrusion Coating		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.41	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	82		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield)	17.9	MPa	ASTM D638
Tensile Elongation ² (Break)	280	%	ASTM D638
Aging	Nominal Value	Unit	
Retention of Tensile Elongation ³ (100°C, 1.14 mm)	94	%	
Retention of Tensile Strength ⁴ (100°C, 1.14 mm)	110	%	
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-31.0	°C	ASTM D746
UL Temperature Rating	60	°C	
Flammability	Nominal Value	Unit	Test Method
Oxygen Index (3.18 mm)	26	%	ASTM D2863
Extrusion	Nominal Value	Unit	
Melt Temperature	154 to 166	°C	
NOTE			
1.	Type IV, 510 mm/min		
2.	Type IV, 510 mm/min		
3.	240 hr, UL Standard		
4.	240 hr, UL Standard		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

