# ALFATER XL® D40E 1GP0000

### Thermoplastic Vulcanizate

#### ALBIS PLASTIC GmbH

#### Message:

ALFATER XL® D40E 1GP0000 is a Thermoplastic Vulcanizate (TPV) product. It can be processed by blow molding or extrusion and is available in Asia Pacific, Europe, or North America. Applications of ALFATER XL® D40E 1GP0000 include automotive, construction applications, electrical/electronic applications, sealing applications and wire & cable.

Characteristics include:

**REACH Compliant** 

**RoHS Compliant** 

Good Weather Resistance

General Information

Features	Alkali Resistant			
	Good Weather Resistance Ozone Resistant			
Uses	Automotive Applications			
	Blow Molding Applications			
	Cable Jacketing			
	Construction Applications			
	Electrical/Electronic Applications			
	Profiles			
	Seals			
Agency Ratings	EC 1907/2006 (REACH)			
RoHS Compliance	RoHS Compliant			
Processing Method	Blow Molding			
	Extrusion			
Physical	Nominal Value	Unit	Test Method	
Density	0.950	g/cm³	ISO 1183	
Hardness	Nominal Value	Unit	Test Method	
Shore Hardness (Shore D)	40		ISO 868	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Stress (100% Strain)	9.80	МРа	ISO 527-2	
Elastomers	Nominal Value	Unit	Test Method	
Tensile Stress (Yield)	20.1	MPa	ISO 37	
Tensile Elongation (Break)	600	%	ISO 37	
Tear Strength	72	kN/m	ISO 34-1	
Compression Set <sup>1</sup> (100°C, 22 hr)	67	%	ISO 815	
Thermal	Nominal Value	Unit		

Service Temperature	-40 to 125	°C	
Injection	Nominal Value	Unit	
Drying Temperature	70.0 to 80.0	°C	
Drying Time	2.0 to 4.0	hr	
Extrusion	Nominal Value	Unit	
Melt Temperature	195 to 215	°C	
NOTE			
1.	25%		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

