

Hifax TKC 243X 3001

Polypropylene Impact Copolymer
LyondellBasell Industries

Message:

Hifax TKC 243X 3001 is a medium flow, 10% mineral filled, high impact polypropylene copolymer for painted exterior applications like bumper fascias. The product is designed especially for injection moulding. It exhibits a good stiffness and an excellent impact strength.

General Information			
Filler / Reinforcement	Mineral,10% Filler by Weight		
Features	Good Stiffness		
	High Impact Resistance		
	Medium Flow		
	Paintable		
Uses	Automotive Bumper		
	Automotive Exterior Parts		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.970	g/cm ³	ISO 1183/A
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	6.0	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield, 23°C)	17.0	MPa	ISO 527-2/50
Tensile Strain			ISO 527-2/50
Yield, 23°C	5.0	%	
Break, 23°C	150	%	
Flexural Modulus ¹ (23°C)	1200	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength			ISO 179/eA
-30°C	6.0	kJ/m ²	
23°C	55	kJ/m ²	
NOTE			
1.	2.0 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

