Quantum Composites QC-8800 FR2X

Vinyl Ester

Quantum Composites Inc.

Message:

QC-8800 FR2X is a vinyl ester based sheet molding compound (SMC) designed for compression molding of components requiring high structural strength and a high level of flame resistance. It exhibits unusual toughness, and is suggested for applications subject to impacts and rough handling. QC-8800 FR2X is also suggested for applications requiring excellent fatigue resistance.

General Information			
Filler / Reinforcement	Glass Fiber,58% Filler by Weight		
Additive	Flame Retardant		
Features	Fatigue Resistant		
	Flame Retardant		
	Good Impact Resistance		
	Good Toughness		
	High Strength		
Appearance	Black		
Forms	SMC - Sheet Molding Compound		
Processing Method	Compression Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.93	g/cm³	ASTM D792
Molding Shrinkage - Flow	0.0	%	ASTM D955
Water Absorption (24 hr)	0.10	%	ASTM D570
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	331	MPa	ASTM D638
Flexural Modulus	17200	MPa	ASTM D790
Flexural Strength	503	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	1800	J/m	ASTM D256
Flammability	Nominal Value		Test Method
Flame Rating (2.03 mm)	V-0		UL 94
Thermoset	Nominal Value	Unit	
Shelf Life (24°C)	8.7	wk	
Demold Time (138°C)	3.0 to 5.0	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

