# ELASTOSIL® R 402/75

#### Silicone

Wacker Chemie AG

### Message:

Silicone Rubber, HTV
Extrudates, Technical, Plastics and Rubber Processing
Extruded parts; tap water and wastewater contact, Plastics and Rubber Processing
Extrudates, food contact, Plastics and Rubber Processing
Cable, general purpose, Plastics and Rubber Processing

General Information	
Features	Food Contact Acceptable
Uses	Compounding
	Potable Water Applications
	Profiles
	Valves/Valve Parts
	Wire & Cable Applications
Processing Method	Extrusion
	Profile Extrusion
	Wire & Cable Extrusion

Uncured Properties	Nominal Value	Unit	Test Method
Color	Clear/Transparent		
Density	1.19	g/cm³	ISO 1183
Cured Properties	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	74		DIN 53505
Tensile Strength	9.30	MPa	DIN 53504
Tensile Elongation at Break	490	%	DIN 53504
Compression Set	62	%	DIN ISO 815-B
Tear Strength	29.0	kN/m	ASTM D624B
Rebound Resilience	49	%	DIN 53512

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

