

STARLEX E/8025-88 naturale

Thermoplastic Polyurethane Elastomer (Polyether)

Daloga srl

Message:

STARLEX E/8025-88 naturale is a Thermoplastic Polyurethane Elastomer (Polyether) (TPU-Polyether) material. It is available in Europe for extrusion. Primary attribute of STARLEX E/8025-88 naturale: Flame Rated.

General Information			
Appearance	Natural Color		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.22 to 1.26	g/cm ³	ISO 1183
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A, 30 sec)	88 to 92		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	28.8 to 35.2	MPa	ISO 527-2
Tensile Strain (Break)	450 to 550	%	ISO 527-2
Abrasion Resistance	47.5 to 52.5	mm ³	DIN 53516
Service Temperature	90	°C	ISO 1183
Thermal Stability	> 80		ISO R 182
Flammability	Passes		CEI 20.35
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	61.8 to 68.3	kN/m	ASTM D624
Thermal	Nominal Value	Unit	Test Method
Ductile / Brittle Transition Temperature	-43.0 to -39.0	°C	ISO 458
Flammability	Nominal Value	Unit	Test Method
Flame Rating	V-0		UL 94
Oxygen Index	26 to 29	%	ISO 4589-2

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT