

Shandong PA6 A1R01

Polyamide 6

Shandong Dongchen Engineering Plastics Co., Ltd.

Message:

Shandong PA6 A1R01 is a Polyamide 6 (Nylon 6) material. It is available in Asia Pacific for pipe extrusion.

Important attributes of Shandong PA6 A1R01 are:

Flame Rated

Good Processability

Good Toughness

Impact Resistant

Typical application of Shandong PA6 A1R01: Plumbing/Piping/Potable Water

General Information		
Features	Good Moldability	
	High Impact Resistance	
	Self Lubricating	
	Ultra High Toughness	
Uses	Corrugated Pipe	
	Piping	
Processing Method	Pipe Extrusion	
Mechanical	Nominal Value	Unit
Tensile Stress (Yield)	50.0	MPa
Tensile Strain (Break)	150	%
Flexural Modulus	1200	MPa
Flexural Stress	60.0	MPa
Impact	Nominal Value	Unit
Charpy Notched Impact Strength	85	kJ/m ²
Charpy Unnotched Impact Strength	No Break	
Flammability	Nominal Value	Test Method
Flame Rating	HB	UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT