

# Marlex® 9503H

High Density (HMW) Polyethylene  
Chevron Phillips Chemical Company LLC

Message:

Marlex® 9503H is a High Density (HMW) Polyethylene material. It is available in Latin America or North America for blow molding or extrusion. Important attributes of Marlex® 9503H are:

Antistatic  
Eco-Friendly/Green  
Food Contact Acceptable  
Hexene Comonomer  
High ESCR (Stress Crack Resistant)  
Typical applications include:  
Containers  
Bottles  
Engineering/Industrial Parts  
Food Contact Applications

General Information			
Additive	Antistatic		
Features	Antistatic		
	Durable		
	Food Contact Acceptable		
	Good Impact Resistance		
	Hexene Comonomer		
	High ESCR (Stress Crack Resist.)		
	High Molecular Weight		
	Recyclable Material		
Uses	Bottles		
	Containers		
	Industrial Containers		
	Industrial Parts		
Agency Ratings	ASTM D 4976-PE235		
	FDA 21 CFR 177.1520(c) 3.1a 2		
Forms	Pellets		
Processing Method	Blow Molding		
	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.946	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.31	g/10 min	ASTM D1238

Environmental Stress-Cracking Resistance (100% Igepal, Compression Molded, F50)	> 800	hr	ASTM D1693B
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength <sup>1</sup> (Yield, Compression Molded)	24.0	MPa	ASTM D638
Tensile Elongation <sup>2</sup> (Break, Compression Molded)	500	%	ASTM D638
Flexural Modulus - Tangent <sup>3</sup> (Compression Molded)	1030	MPa	ASTM D790
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	< -75.0	°C	ASTM D746A
NOTE			
1.	Type IV, 51 mm/min		
2.	Type IV, 51 mm/min		
3.	13 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT