

POLYPRO® 5014L HPT-H

Polypropylene Homopolymer

YUHWHA Korea Petrochemical Ind. Co., Ltd.

Message:

POLYPRO® 5014L HPT-H is a Polypropylene Homopolymer (PP Homopolymer) material. It is available in Asia Pacific.

Important attributes of POLYPRO® 5014L HPT-H are:

High Purity

Homopolymer

Typical application of POLYPRO® 5014L HPT-H: Film

General Information			
Features	General Purpose		
	High Purity		
	Homopolymer		
	Non-Smooth Surface Finish		
Uses	Film		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	3.8	g/10 min	ASTM D1238
Ash Content - XRF	10 to 20	ppm	Internal Method
Catalyst Residue			Internal Method
AI (XRF)	2 to 4	ppm	
CI (XRF)	1 to 3	ppm	
Isotactic Index	96	%	Internal Method
Thermal	Nominal Value	Unit	Test Method
Peak Melting Temperature	162 to 165	°C	ASTM D3418
Electrical	Nominal Value		Test Method
Dielectric Constant	2.25		Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co., Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT