

Caltex PP MT42TB

Polypropylene

GS Caltex

Message:

Caltex PP MT42TB is a Polypropylene material. It is available in Asia Pacific.
Typical application of Caltex PP MT42TB: Engineering/Industrial Parts

General Information			
UL YellowCard	E319107-100074943	E119841-220400	E352041-101083982
Features	Paintable		
Uses	Shock Absorbing Pads		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.04	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	6.0	g/10 min	ASTM D1238
Molding Shrinkage			ASTM D955
Flow	0.85	%	
Across Flow	0.80	%	
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	68		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	19.6	MPa	ASTM D638
Tensile Elongation (Break)	450	%	ASTM D638
Flexural Modulus	1860	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
--	450	J/m	
-30°C	64	J/m	
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	129	°C	ASTM D648
Additional Information	Nominal Value	Unit	
Processing Temperature	210 to 230	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

