Sylvin 8699-75 Clear 876

Polyvinyl Chloride

Sylvin Technologies Incorporated

Message:

Sylvin 8699-75 Clear 876 Is A Vinyl Compound Formulated For Extrusion Applications To Improve Heat Stability. This Compound Contains A Polymeric Plasticizer For Low Migration And Increased Chemical Resistance.

General Information			
Additive	Heat Stabilizer		
	Plasticizer		
Features	Good Chemical Resistance		
	Heat Stabilized		
	Low to No Migration		
	Plasticized		
Appearance	Clear/Transparent		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.25	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	75		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	14.5	MPa	ASTM D638
Tensile Elongation (Break)	400	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	59.5	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	163 to 174	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

