SQUARE® LSR6929-70AFC/BFC

Silicone Rubber, LSR

Shenzhen SQUARE Silicone Co., Ltd.

Message:

Silicone rubber for cellphone keypad products cured fast under low temperature
Product description
The product is one kind of 2-part liquid silicone rubber catalyzed by platinum, fast cure below 120, mixing ratio of parts A:B=1:1, suitable for making P+R
cellphone keypad.
Key features
Fast cure undre low temperature
High transparent
Good rebound property
Non-Toxic and odorless
Application
Suitable for making P+R cellphone keypad

General Information				
Features	Fast curing			
	The smell is low to none			
	Definition, high			
	Non-toxic			
Uses	Mobile phone			
Appearance	Clear/transparent			
Physical	Nominal Value	Unit	Test Method	
Molding Shrinkage - Flow	2.0	%		
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A)	65		ASTM D2240	
Elastomers	Nominal Value	Unit	Test Method	
Tensile Strength	7.00	MPa	ASTM D412	
Tensile Elongation (Break)	340	%	ASTM D412	
Tear Strength ¹	30.0	kN/m	ASTM D624	
Thermoset	Nominal Value	Unit	Test Method	
Thermoset Components				
Component a	Mixing ratio by weight: 1.0			
Component B	Mixing ratio by weight: 1.0			
Shelf Life	52	wk		
Uncured Properties	Nominal Value	Unit	Test Method	
Viscosity	900	Pa·s	DIN 53019	
NOTE				
1.	B mould			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

