

# VisiJet® FTX Green

Unspecified

3D Systems

Message:

UV Curable Plastic  
Tough castable plastic

General Information			
Features	Clean/High Purity		
Uses	Modeling Material		
	Mold Making		
	Prototyping		
Appearance	Dark Green		
Forms	Liquid		
Processing Method	3D Printing, Stereolithography		
Physical	Nominal Value	Unit	
Density <sup>1</sup>	1.01	g/cm <sup>3</sup>	
Ash Content	0.010	%	
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	1700	MPa	ASTM D638
Tensile Strength	30.0	MPa	ASTM D638
Tensile Elongation (Break)	10	%	ASTM D638
Flexural Strength	40.0	MPa	ASTM D790
NOTE			

1. Liquid @ 25°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT