

# KEP® 960N(F)

Ethylene Propylene Diene Terpolymer

Kumho Polychem Co., Ltd.

## Message:

### Features:

Non-aromatic paraffinic oil, high mooney viscosity & high ethylene content, high filler loading & good physical properties

### Applications:

Radiator hose, window seals, extruded goods in general, automobile parts, moldings, washing machine gasket

General Information	
Features	High Viscosity
Uses	Automotive Applications
	Gaskets
	Hose
	Seals
Forms	Bale
Processing Method	Extrusion
	Injection Molding

Physical	Nominal Value	Unit
Mooney Viscosity (ML 1+8, 125°C)	49	MU
Ethylene Content	70.0	wt%
Ethylidene Norbornene (ENB) Content	5.7	wt%
Oil Type (Unspecified Oil)	50.0	phr

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co., Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

