

# PETOPLEN EH 161

Polypropylene

PETKIM Petrokimya Holding A.S.

## Message:

PETOPLEN EH 161 is a polypropylene product. It can be processed by injection molding and is available in North America, Europe or the Asia-Pacific region. PETOPLEN EH 161 applications include hats/caps/corks and consumer goods.

General Information			
Uses	Shield Toys		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	14 - 19	g/10 min	ASTM D1238
Color b <sup>1</sup>	1.60		
Contamination <sup>2</sup>		pcs/100 g	
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	36.0	MPa	ASTM D638
NOTE			
1.	Hunter Lab CQ, 10D65		
2.	TM-113		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

