

TEKALOY™ G70A4

Polycarbonate + ABS

Mando Advanced Materials Co., Ltd.

Message:

TEKALOY™ G70A4 is a Polycarbonate + ABS (PC+ABS) product. It is available in Asia Pacific.

Characteristics include:

Flame Rated

Impact Resistant

General Information			
Features	Low Temperature Impact Resistance		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.14	g/cm ³	ASTM D792
Molding Shrinkage ¹			ASTM D955
Flow	0.60	%	
Across Flow	0.60	%	
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	58.8	MPa	ASTM D638
Tensile Elongation (Break)	> 100	%	ASTM D638
Flexural Modulus	2110	MPa	ASTM D790
Flexural Strength	76.5	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	640	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	113	°C	ASTM D648
Flammability	Nominal Value		Test Method
Flame Rating	HB		UL 94
Injection	Nominal Value	Unit	
Processing (Melt) Temp	220 to 290	°C	
Mold Temperature	60.0 to 90.0	°C	
NOTE			
1.	60°C Mold Temperature		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

