

Taitacell EPS 321LF

Expanded Polystyrene

Taita Chemical Company, Ltd.

Message:

Taitacell EPS 321LF is an Expanded Polystyrene material. It is available in Asia Pacific or North America.

Important attributes of Taitacell EPS 321LF are:

Flame Rated

Flame Retardant

Typical applications include:

Wire & Cable

Construction Applications

Packaging

General Information			
Additive	Flame Retardant		
Features	Flame Retardant		
Uses	Construction Applications		
	Insulation		
	Packaging		
Agency Ratings	UL 723		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	> 0.0190	g/cm³	ASTM D792
Pentane Content	< 5.0	%	
Water Content	< 0.50	%	
Bead Size ¹	500.0 to 850.0	µm	
Chemical Resistance			
Acid	Good		
Alkali	Good		
Solvent	Poor		
Expandability	25.0 to 65.0		
Mechanical	Nominal Value	Unit	Test Method
Flexural Strength	> 0.294	MPa	ASTM D790
Compressive Strength (10% Strain)	> 0.0785	MPa	ASTM D695
Thermal	Nominal Value	Unit	Test Method
Thermal Conductivity	0.031 to 0.042	W/m/K	ASTM C177
Flammability	Nominal Value		Test Method
Flame Rating	HF-1		UL 94
NOTE			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT