

# HydroSlip™ C

Polyurethane (Polyether based)  
AdvanSource Biomaterials Corp.

Message:

HydroMed D is a series of ether-based hydrophilic urethanes with excellent adhesive and cohesive properties while exhibiting tailored water absorption levels depending upon end product targets.

This material does not require UV curing and as such, provides a superior alternative to UV curable materials for devices which require inner lumen or complicated form coatings.

These materials were designed for use as coatings for a wide array of devices including catheters, guidewires, sutures, introducers, rods, and valves. The HydroMed series can also be coated onto devices to reduce the absorption of white cells and proteins, thereby aiding in the analysis of blood and DNA.

HydroMed is processed by traditional solvent coating methods. The polymer granules can be dissolved in varying concentrations using most organic and inorganic solvent packages.

AdvanSource Biomaterials synthesizes and manufactures medical grade materials offering the ability to tailor physical and mechanical characteristics to support and enhance your end product design.

These mechanical characteristic's, critical to the design and development of medical devices, can incorporate a wide range of physical and chemical properties while maintaining core characteristics such as biodurability and biocompatibility. In most materials, specialized characteristics such as the addition of colorant agents or antimicrobial properties (where applicable) can be added to the polymer to provide a homogenous material and limit secondary processing steps.

In addition, radiopaque agents may also be incorporated into the formula to provide additional product enhancements and may contain up to 40%, by weight, of a radiopaque agent thus allowing varied-scale visibility options.

With an expanding range of secondary operations including custom solution development, prototype coating capabilities, and project management services, ASB's expert team of chemists, scientists, engineers and industry professionals assist in every stage of customers' projects, from concept initiation through full-scale manufacture.

General Information		
Additive	High Slip	
Features	Biocompatible	
	Good Adhesion	
	High Elongation	
	High Slip	
	Hydrophilic	
	Low Friction	
	Lubricated	
Uses	Coating Applications	
	Medical/Healthcare Applications	
	Valves/Valve Parts	
Agency Ratings	EU 1999/534/EC	
Forms	Granules	
Processing Method	Solution Coating	
Physical	Nominal Value	Unit
Water Content	95	%
Linear Expansion	180	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

