

VINIKA® T133D

Rigid Polyvinyl Chloride

Mitsubishi Chemical Performance Polymers, Inc.

Message:

VINIKA® T133D is a Rigid Polyvinyl Chloride material. It is available in Asia Pacific for extrusion. Primary attribute of VINIKA® T133D: Heat Resistant.
Typical application of VINIKA® T133D: Construction Applications

General Information			
Features	High Heat Resistance		
Uses	Building Materials		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.45	g/cm ³	JIS K7112
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	45.0	MPa	JIS K7161
Tensile Strain (Break)	90	%	JIS K7161
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength	16	kJ/m ²	JIS K7111
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	114	°C	JIS K7206 ¹
NOTE			

1. A (10N)

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

