

# EPAMOULD 786A33

Thermoplastic Polyurethane Elastomer (Polyether)

Epaflex Polyurethanes S.R.L.

## Message:

The EPAMOULD 700 series includes products based on polyether. This allows polyurethanes which have excellent resistance to hydrolysis, resistance to microbial attack without the use of special additives, and good flexibility at very low temperatures.

General Information		
Additive	Beeswax	
Features	Flexibility at low temperatures	
	Antimicrobial	
	Hydrolysis resistance	
Physical	Nominal Value	Unit
Density	1.14	g/cm <sup>3</sup>
Hardness	Nominal Value	Unit
Durometer Hardness (Shore A)	86	
Mechanical	Nominal Value	Unit
Abrasion Loss	65.0	mm <sup>3</sup>
Flammability	Nominal Value	Test Method
Flame Rating	V-2	UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT