

VESTOLIT® M 5960

Polyvinyl Chloride
VESTOLIT GmbH & Co. KG

Message:

VESTOLIT M 5960 - is a free-flowing mass(M) PVC with a narrow particle size distribution. It is suitable for extrusion, injection moulding and calendering.

General Information			
Uses	Bottles		
	Containers		
	Film		
	Piping		
	Profiles		
	Sheet		
Processing Method	Blow Molding		
	Calendering		
	Extrusion		
	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.60	g/cm ³	ISO 60
K-Value	59.0		ISO 1628-2
Sieve Analysis			ISO 4610
-- 1	< 2.0	%	
-- 2	> 93	%	
Volatiles	< 0.30	%	ISO 1269
NOTE			
1.	retained on 0.020 mm sieve		
2.	retained on 0.063 mm sieve		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 1342475533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT