

Yuyao PPO LED

Polyphenylene Ether + PS

Yuyao Tenglong Plastics Co., Ltd.

Message:

Yuyao PPO LED is a Polyphenylene Ether + PS (PPE+PS) product. It is available in Asia Pacific. Typical application: Lighting Applications.

Characteristics include:

Flame Rated

RoHS Compliant

Good UV Resistance

General Information			
Features	Good UV Resistance		
Uses	LEDs		
RoHS Compliance	RoHS Compliant		
Appearance	Opaque		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.20	g/cm ³	ASTM D792
Molding Shrinkage - Flow	0.50 to 0.80	%	ASTM D955
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	70.0	MPa	ASTM D638
Tensile Elongation (Break)	4.0	%	ASTM D638
Flexural Modulus	4200	MPa	ASTM D790
Flexural Strength	120	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (Area)	7.00	kJ/m ²	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	122	°C	ASTM D648
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity	2.3E+3	ohms · cm	ASTM D257
Flammability	Nominal Value	Unit	Test Method
Flame Rating			UL 94
1.60 mm	HB		
3.20 mm	HB		
Injection	Nominal Value	Unit	Test Method
Drying Temperature	100 to 115	°C	
Drying Time	4.0 to 5.0	hr	
Processing (Melt) Temp	250 to 280	°C	
Mold Temperature	60.0 to 80.0	°C	
Injection Pressure	70.0 to 100	MPa	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any

infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

