# KumhoSunny ABS 744

### Acrylonitrile Butadiene Styrene

Shanghai KumhoSunny Plastics Co., Ltd.

#### Message:

ABS744 is Injection grade ABS resin with a super high impact. ABS744 is mainly used in skis, golf club heads, sports equipment, etc.

General Information				
Features	Ultra High Impact Resistance			
Uses	Sporting Goods			
UL File Number	E254819			
	E65424			
Forms	Pellets			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.04	g/cm³	ASTM D792	
Melt Mass-Flow Rate (MFR) (220°C/10.0				
kg)	16	g/10 min	ASTM D1238	
Molding Shrinkage - Flow	0.30 to 0.60	%	ASTM D955	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength	38.0	MPa	ASTM D638	
Tensile Elongation (Break)	40	%	ASTM D638	
Flexural Modulus	1800	MPa	ASTM D790	
Flexural Strength	58.0	МРа	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact (3.20 mm)	580	J/m	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load (1.8				
MPa, Unannealed)	80.0	°C	ASTM D648	
Vicat Softening Temperature	92.0	°C	ASTM D1525 <sup>1</sup>	
Electrical	Nominal Value	Unit	Test Method	
Surface Resistivity	> 1.0E+14	ohms	IEC 60093	
Volume Resistivity	> 1.0E+14	ohms·cm	IEC 60093	
Flammability	Nominal Value	Unit	Test Method	
Flame Rating	НВ		UL 94	
Injection	Nominal Value	Unit		
Drying Temperature	80.0 to 90.0	°C		
Drying Time	3.0 to 4.0	hr		
Suggested Max Moisture	0.050	%		
Rear Temperature	190 to 200	°C		
Middle Temperature	200 to 220	°C		

Front Temperature	210 to 230	°C	
Nozzle Temperature	210 to 230	°C	
Processing (Melt) Temp	200 to 230	°C	
Mold Temperature	50.0 to 80.0	°C	
Back Pressure	1.00 to 5.00	MPa	
Screw Speed	30 to 60	rpm	
NOTE			
1.	Rate B (120°C/h)		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

